



ULTIMATE STRENGTH RATING 72kN
 POLE SPECIFICATION
 STOCK CODE 414255
 LENGTH 12.5m
 DIAMETER 457mm
 WALL THICKNESS 9.8mm
 EMBEDMENT DEPTH 2.4m
 GROUND LEVEL PROTECTION 1.0m
 0.5m ABOVE GROUND LEVEL
 0.5m BELOW GROUND LEVEL

DISTANCE FROM TOP (mm)	HOLE DIAMETER (mm)									
	0°	45	60	90	135	180	225	270	300	315
120	26					26				
220				26				26		
320		26			26		26			26
720	26					26				
820				26				26		
920		26			26		26			26
950			M16						M16	
1320	26					26				
1400	M12		M16			M12				
1420				26				26		
1520		26			26		26			26
1850									M16	
1920	26					26				
2020				26				26		
2120		26			26		26			26
2300	M12		M16			M12			M16	
2520	26					26				
2750									M16	
2900	26					26				
3100	26					26				
3200	M12		M16			M12			M16	
3220				26				26		
3400	M12									
3650									M16	
3750	26					26				
3820				26				26		
4320	26					26				
4420				26				26		
4900	M12									
7000	M12			M12		M12		M12		
8000	M12			M12		M12		M12		
8900	M12			M12		M12		M12		
9000	TOP OF GL									
9500	EMBEDMENT									
10000	BOTTOM OF GL									

NO	DESCRIPTION	DRN	DATE	CKD	APPD
0	ISSUED FOR CONSTRUCTION	C.C.	AUG'11	A.T.	S.C.
AMENDMENTS					



DES	A.T.	POWER STANDARD DRAWING		
DRN	C.C.	POLES ROUND LINE 12.5D BOLTED CONNECTIONS TYPE		
CKD	A.T.			
APPD	S.C.			
SCALE	N.T.S.			
ISSUED	AUG'11	A3	DRAWING NUMBER	S01-1-1-26
ALL DIM. IN mm				
DRAFTING STANDARD TO A.S.1100		CAD PRODUCT - DO NOT AMEND MANUALLY		AMDT