



ULTIMATE STRENGTH RATING 16kN
 POLE SPECIFICATION
 STOCK CODE 414254
 LENGTH 12.5m
 DIAMETER 323mm
 WALL THICKNESS 4.7mm
 EMBEDMENT DEPTH 2.4m
 GROUND LEVEL PROTECTION 1.0m
 0.5m ABOVE GROUND LEVEL
 0.5m BELOW GROUND LEVEL

DISTANCE FROM TOP (mm)	HOLE DIAMETER (mm)									
	0°	45	90	120	135	180	225	240	270	315
120	26					26				
220			26						26	
320		26			26		26			26
720	26					26				
820			26						26	
920		26			26		26			26
950			M16						M16	
1320	26					26				
1400	M12			M16		M12				
1420			26						26	
1520		26			26		26			26
1850									M16	
1920	26					26				
2020			26						26	
2120		26			26		26			26
2300	M12		M16			M12			M16	
2520	26					26				
2750									M16	
2900	26					26				
3100	26					26				
3200	M12		M16			M12			M16	
3220			26						26	
3650									M16	
3720	26					26				
3800	M12									
3820			26						26	
4320	26					26				
4420			26						26	
5800	M12									
7900	M12		M12	M12				M12	M12	
8900	M12		M12	M12				M12	M12	
9800	M12		M12			M12			M12	
9900	TOP OF GL									
10400	EMBEDMENT									
10900	BOTTOM OF GL									

NO	DESCRIPTION	DRN	DATE	CKD	APPD
0	ISSUED FOR CONSTRUCTION	C.C.	SEP'11	A.T.	S.C.
AMENDMENTS					



DES	A.T.	POWER STANDARD DRAWING		
DRN	C.C.	POLES ROUND LINE 12.5C BOLTED CONNECTIONS TYPE		
CKD	A.T.			
APPD	S.C.			
SCALE	N.T.S.			
ISSUED	SEP'11	A3	DRAWING NUMBER	S01-1-1-27
ALL DIM. IN mm				
DRAFTING STANDARD TO A.S.1100		CAD PRODUCT - DO NOT AMEND MANUALLY		AMDT