

NOTES:

- SIGN IS FOR OUTDOOR USE UNDER EXTREME TROPICAL CONDITIONS AND MUST HAVE A LIFE EXPECTANCY OF 20 YEARS.
- 2. MATERIAL TO BE 2.0 ANODIZED ALUMINIUM
- 3. APPLY TWO COATS OF SUITABLE PAINT OR INK. THE FINISHED SIGN MUST BE DIPPED IN A CLEAR LAQUER TWO COATS
- 4. COLOUR:

BACKGROUND: WHITE GENERAL TEXT: PANTONE 294C POWERWATER LOGO: PANTONE 294C AND PANTONE 392C AS SHOWN MANUFACTURER LOGO: AS REQUIRED

5. GENERAL TEXT TO BE CALIBRI

32 X 25 ALUMINIUM LIPPED CHANNEL STIFFENERS POP RIVETTED TO SHEET AT 250 CENTRES

NO	DESCRIPTION	DRN	DATE	CKD	APPD
NO.	DESCRIPTION	DOM	DATE	CVD	ADDO
14 13 12 11 10 9	ALL NOTES REWRITTEN. TITLEBLOCK & DRAWING NUMBER FORMATTED POWERWATER NOTES AND DIMENSIONS CHANGED REDRAWN ON CAD AND "POWERWATER" INSTEAD OF "PAWA" TITLE AND DRAWING No. CHANGED REDRAWN AND REDESIGNED	A.N. K.T. K.I. A.S. Q.L.J. W.T.	FEB'22 FEB'19 FEB'05 NOV'02 MAY'88 JUNE'87	B.V. C.C. R.C. R.C.	B.C. C.C. C.C. M.B. -



DES	-		POWER	STANDARD	DRAWING				
DRN	A. SCHMID								
CKD	M. BOCK	SIGNS							
APPD	M. BOCK	MAJOR INSTALLATIONS							
SCALE	1 : 10.								
ISSUED	NOV'02	А3	DRAWING	CA2 A1	00 16				
ALL DIM.	IN mm	AS	NUMBER	S02-01	-08-16	<u> </u>			
DRAFTING STANDARD TO A.S.1100			CAD PRODUCT	- DO NOT AMEN	ND MANUALLY	AMDT			