

## NOTES:

- 1. SIGN IS FOR OUTDOOR USE UNDER EXTREME TROPICAL CONDITIONS AND MUST HAVE A MINIMUM LIFE EXPECTANCY OF 20 YEARS.
- 2. MATERIAL TO BE 2.0 mm ANODIZED ALUMINIUM.
- 3, SIGN TO BE IN ACCORDANCE WITH AS1319 UNLESS OTHERWISE SPECIFIED. ANY GRAPHIC SYMBOL IS TO BE IN ACCORDANCE WITH AS1104.
- 4. LETTERING TO BE SERIES 'D' TO AS1744. HEIGHT: 'DANGER' - 30 mm OTHER WORDING SIZE TO BE 14mm MINIMUM.
- 5, FINISH SHALL BE 1 COAT PRIMER, 2 COATS (PER COLOUR) OF VITREOUS ENAMEL PAINT TO AS4025 PARTS 1 & 4 3M SCOTCHLITE CLASS 2 SHEETING AND 3M INKS TO GIVE A LIFE EXPECTANCY OF 5 YEARS MINIMUM. ALTERNATIVE FINISHES WILL BE CONSIDERED PROVIDED THAT SUCH FINISHES ARE CAPABLE OF WITHSTANDING SEVERE TROPICAL CONDITIONS ESPECIALLY ULTRA-VIOLET LIGHT, WHERE ALTERNATIVE FINISHES ARE PROPOSED, COMPLETE TECHNICAL INFORMATION AND DETAILS OF PERFORMANCE SHALL BE PROVIDED TO FACILITATE TECHNICAL ASSESSMENT.
- 6. COLOUR:

BACKGROUND : WHITE

DANGER PANEL : WHITE LETTERS ON RED OVAL SHALL BE ON A BLACK BACKGROUND WITH WHITE BORDER

DEFINING THE OVAL. THERE SHALL BE A NARROW BLACK BORDER AROUND THE PERIMETER OF THE SIGN. ALL DTHER WORDING TO BE IN BLACK.

RED BACKGROUND : SIGNAL RED TO CODE R13 IN ACCORDANCE WITH AS2700.

7. STDCK CODE .....

1	APPROVED FOR CONSTRUCTION.	RGI	SEP'99	MWB	FRI
NO	DESCRIPTION	DRN	DATE	CKD	APF



DES	M.BOCK	
DRN	R. INNES	
CKD	S.SAWYER	
APPD	F.ROBSON	
SCALE	1:1.25	
ISSUED	20/10/97	Г

DRN	R. INNES
CKD	S.SAWYER
APPD	F.ROBSON
SCALE	1:1.25
ISSUED	20/10/97

ALL DIM. IN mm

SINGLE WIRE FARTH RETURN EARTHING DANGER SIGN POLE MOUNTED

DRAWING NUMBER

S25-3-2-03



AMENDMENTS

NORTHERN TERRITORY

DRAFTING STANDARD TO A.S.1100

POWER STANDARD DRAWING

CAD PRODUCT - DO NOT AMMEND MANUALLY