

DETAIL OF SLEEVE

95sq.mm SLEEVE SHOWN.

TABLE 1: ITEM DETAILS

ITEM	CONDUCTOR C.S.A	RATED TENSION	HEX. DIE A/F	ITEM
REF.	(sq.mm)	(kN)	(mm)	NUMBER
1	95	16.8	21.5	229039
2	95	7	17.3	206664
3	150	7	21.5	415590

NOTES:

- CABLE INSULATION TO BE REMOVED TO DIMENSION SHOWN ON LINK AND FULLY INSERTED INTO LINK BEFORE COMPRESSION.
- 2. JOINTS TO BE MADE WITH INDIVIDUAL CORE JOINTS STAGGERED MIN 150mm.
- 4. LINK TO HAVE EMBOSSED ON THE INSULATION:
 - STRIPPING LENGTH,
 - COMPRESSION DIE SIZE A/F,
 - NUMBER, LOCATION AND SEQUENCE OF COMPRESSIONS.
- 5. TO COMPLY WITH PWC SPECIFICATION STSP 05-013.

		-			_
NO	DESCRIPTION	DRN	DATE	CKD	APPD
1	REDRAWN ON CAD AND REVISED	R.T.F	OCT'89	1	G.S.
2	NOTE 5 ADDED, DIMENSIONS 'A' AND 'B' REMOVED.	K.T.	MAY'98	R.I.	F.R.
3	TABLE AND NOTE 4 AMENDED	K.T.	NOV'99	G.H.	F.R.
4	AMENDED NOTES	K.T.	FEB'08	B.C.	S.C.
5	150sqmm VERSION ADDED	K.T.	MAR'12	B.C.	S.C.
6	NOTE 3 TITLEBLOCK & DRAWING NUMBER FORMATTED	K.T.	DEC'19	C.C.	C.C.
7	REFORMATTED TABLE & TEXT. CHANGED ITEM 2 A/F. REMOVED COLOURS &	A.N.	AUG'21	A.N.	B.V.
8	AMENDED ITEM 3. ADDED NOTE 5.	P.BH.	NOV'22	B.V.	B.C.



DES	A.B.	POWER STANDARD DRAWING					
DRN	A.DAVIS						
CKD	R.INNES	LV AERIAL BUNDLED CABLE LINK - COMPRESSION					
APPD	F.ROBSON						
SCALE	N.T.S.						
ISSUED	MAY'98	A3	DRAWING	COA OA OO 47			
ALL DIM	1. IN mm	AS	NUMBER	S04-01-02-17			
DRAFTING STANDARD TO A.S.1100			CAD PRODUCT	- DO NOT AMEND MANUALLY	AMDT		