



PAGE : 1 OF 1
DATE : 8/12/93
REVISION : ONE
DISTRIBUTION : VOLUME 1 HOLDERS
PREPARED BY : ALAN BUTLER
AUTHORISED BY : TONY GREENWOOD

**STANDARDS BRANCH
- Power Division**

STANDARDS BULLETIN No. : S1-052

EARTHING - CRIMP CONNECTIONS

SUBJECT:

A new style earthing system has been introduced with compression fittings taking the place of bolted clamps.

These connectors are called Profile '6', and Profile 'C'.

1. Profile '6'

A copper compression connector for use where connection between 14 mm Earth Rods, and 70 or 95 mm² conductor is required.
See Drawing S1-2-3-14. Item 1 & 2.

2. Profile 'C'

A copper compression connector for use where connection between 70 & 95 mm² conductor is required. See drawing S1-2-3-14. Item 3 & 4.

Please note all Earth Rods will have a 30 mm section of one end double Knurled at the factory, to stop rotation of clamps. Drawing S1-1-5-1 Item 2 refers.

Assemblies are shown on Drawings S1-2-3-11, S1-2-3-12 and S1-2-3-13.

A. Greenwood.

TONY GREENWOOD
STANDARDS DEVELOPMENT ENGINEER