


NOTES:

1. MATERIAL TO BE ZE25/25-A-PC (ZINC COATED STEEL) 3mm THICK.
2. FINISH TO BE PAINTED MATT BLACK
3. ASSEMBLY CONSISTS OF 2 PARTS, TO BE SUPPLIED BOLTED TOGETHER WITH M8 HEX HEAD SCREWS WITH WASHERS.
4. ALTERNATE CONSTRUCTION WITH STANDARD SHS AND PFC WILL BE CONSIDERED.

DRILL AND FIT 4 OFF M8 NUT WELDED BEHIND



3

ø10 4 OFF

0	ISSUED FOR CONSTRUCTION	A.N.	NOV'20	C.C.C.	B.C.
NO	DESCRIPTION	DRN	DATE	CKD	APPD
AMENDMENTS					



DES	PWC	POWER STANDARD DRAWING			
DRN	A. NATHAN	RM6 RMU ETSA STEEL PLINTH			
CKD	C. CAMILLERI				
APPD	B. CHEUNG				
SCALE	N.T.S.				
ISSUED	NOV'20	A3	DRAWING NUMBER	S02-01-04-30	
ALL DIM.	IN mm			CAD PRODUCT - DO NOT AMEND MANUALLY	
DRAFTING STANDARD TO A.S.1100					