

TABLE 1: GENERAL PURPOSE INSULATION SLEEVE

GREEN/YELLOW (1.2m LENGTHS)		RED (1.2m LENGTHS)		WHITE (1.2m LENGTHS)		BLUE (1.2m LENGTHS)		BLACK (1.2m LENGTHS)		NOMINAL SIZE (mm)	INSIDE DIAMETER (mm)		NOMINAL RECOVERED WALL THICKNESS (mm)
ITEM REF.	ITEM NUMBER	ITEM REF.	ITEM NUMBER	ITEM REF.	ITEM NUMBER	ITEM REF.	ITEM NUMBER	ITEM REF.	ITEM NUMBER		EXPANDED (MIN)	RECOVERED (MAX)	
-	-	45	410610	46	410609	47	410605	-	-	9.5	9.5	4.8	0.62
48	410602	4	4093	5	4101	6	4127	7	4382	19	19.1	9.5	0.76
49	502290	8	4143	9	4150	10	4168	11	4408	25	25.4	12.7	0.89
50	410600	12	4184	13	4192	14	4218	15	4424	38	38.1	19.1	1.02
30	287078	16	4259	17	4275	18	4283	19	4440	50	50.8	25.4	1.14
-	-	20	4291	21	4317	22	4333	23	4457	76	76.2	38.1	1.27
-	-	24	4341	25	4358	26	4366	27	4465	102	101.6	50.8	1.40

TABLE 2: HEAVY WALL CABLE SLEEVE (ADHESIVE COATED)'

ITEM REF.	ITEM NUMBER	LENGTH	INSIDE DIAMETER (mm)		WALL THICKNESS (mm)	
			EXPANDED (MIN)	RECOVERED (MAX)	AS SUPPLIED	RECOVERED (NOM)
1	3129	1200	51	16	1.3	4.1
2	3145	1200	90	30	1.3	4.1
3	3152	1200	120	40	1.3	4.2

TABLE 3: MEDIUM WALL CABLE SLEEVE (ADHESIVE COATED)'

ITEM REF.	ITEM NUMBER	LENGTH	INSIDE DIAMETER (mm)		WALL THICKNESS (mm)	
			EXPANDED (MIN)	RECOVERED (MAX)	AS SUPPLIED	RECOVERED (NOM)
31	3202	300	10	3	0.3	0.9
32	3210	1200	50	16	0.5	1.9
33	3228	250	35	12	0.4	1.9
34	3269	250	75	22	0.6	2.7
35	4564	250	16	5	0.3	1.4

TABLE 4: END CAPS
(SEALANT COATED HEAT SHRINK)

ITEM REF.	ITEM NUMBER	CABLE DIA.	LENGTH
36	4853	17 - 30	90
37	4879	45 - 65	170
38	4887	65 - 95	163
39	4804	4 - 8	34
40	4820	11 - 17	55
51	4838	7.5 - 20	55

TABLE 5: END CAPS (COLD SHRINK)

ITEM REF.	ITEM NUMBER	CABLE DIA.	LENGTH
41	-	11.6-20.9	55
42	501820	15.9-30.1	55
43	501821	26.0-49.2	55
44	501822	45.5-84.3	55

NOTES:

FOR TUBING ONLY (TABLES 1, 2 & 3)


1. TEMPERATURE RATINGS

A. GENERAL PURPOSE INSULATION SLEEVE :
 - CONTINUOUS FROM -55°C TO +135°C
 - SHORT TERM AT +300°C

B. HEAVY AND MEDIUM WALL SLEEVE :
 - CONTINUOUS AT 90°C
 - SHORT TERM AT 135°C.

' INDICATES ADHESIVE IS HOT MELT POLYMER FOR HEAVY AND MEDIUM WALL SLEEVING.

2. FOR FURTHER TECHNICAL REQUIREMENTS REFER TO STANDARD TECHNICAL SPECIFICATIONS STSP 05-005 & STSP 05-006.

20	REFORMATED TABLES. UPDATED NOTE 2, TITLE & TABLE NUMBERS. ADDED ITEMS 42-51, ITEM NUMBERS AND LENGTH. REMOVED ITEM 29.	A.N.	AUG'21	C.C.C.	B.V.	DES -	POWER STANDARD DRAWING		
							NO	DESCRIPTION	DRN E.S.L
19	TITLEBLOCK & DRAWING NUMBER FORMATTED	K.T.	JAN'19	C.C.	C.C.	ALL DIM. IN mm			
18	END CAPS (COLD SHRINK) DATA ADDED	K.I.	AUG'05	C.C.	C.C.				
17	DIMENSIONS CHANGED ON MEDIUM WALL TUBING.	J.A.L.	JAN'97	A.B.	F.R.R.				
AMENDMENTS						 NORTHERN TERRITORY			