

NOTES:

4

5.

6

20

20

50

23

- 2.
- 3. SIGN TO BE IN ACCORDANCE WITH AS 1319 UNLESS OTHERWISE SPECIFIED.
 - HEIGHT: 'DANGER' 20 mm
 - OR
 - COLOUR BACKGROUND: WHITE

DRAFTING STANDARD TO A.S.1100		
ALL DIM. IN mm A3		
ISSUED	JULY 1984	د ۸
SCALE	AS SHOWN	
APPD	I.CUK	GENE
CKD	R.HAIGH	PORT
DRN	G.A.WADE	SIGNS
DES	R.HAIGH	

Α3	DRAWING NUMBER	S02-01-08-02	
A.S.1100	CAD PRODUCT - DO NOT AMEND MANUALLY		



ABLE RAL DANGER

POWER STANDARD DRAWING

DANGER PANEL: WHITE LETTERS ON RED OVAL SHALL BE ON A BLACK BACKGROUND WITH WHITE BORDER DEFINING THE OVAL THERE SHALL BE A NARROW BLACK BORDER AROUND THE PERIMETER OF THE SIGN. ALL OTHER WORDING TO BE IN BLACK. RED BACKGROUND: SIGNAL RED TO CODE R13 IN ACCORDANCE WITH AS 2700.

ALTERNATIVE FINISHES WILL BE CONSIDERED PROVIDED THAT SUCH FINISHES ARE CAPABLE OF WITHSTANDING SEVERE TROPICAL CONDITIONS ESPECIALLY ULTRA-VIOLET LIGHT. WHERE ALTERNATIVE FINISHES ARE PROPOSED COMPLETE TECHNICAL INFORMATION AND DETAILS OF PERFORMANCE SHALL BE PROVIDED TO FACILITATE TECHNICAL ASSESSMENT.

3M SCOTCHLITE CLASS 2 SHEETING AND 3M INKS TO GIVE A LIFE EXPECTANCY OF 5 YEARS MINIMUM.

FINISH SHALL BE 1 COAT PRIMER 2 COATS (PER COLOUR) OF VITREOUS ENAMEL PAINT TO AS 4025 PARTS 1 & 4 $\!\!\!$

OR 18 mm MINIMUM FOR 3 ROWS OF TEXT. TEXT AND COLOUR BLOCK OVER WHITE BACKGROUND

TABLE 01 WORDING SIZE TO BE 25 mm MINIMUM FOR 1 & 2 ROWS OF TEXT

LETTERING TO BE SERIES 'D' TO AS 1744

ANY GRAPHIC SYMBOL IS TO BE IN ACCORDANCE WITH AS 1104

MATERIAL TO BE 2.0 mm ANODIZED ALUMINIUM

SIGN MUST HAVE A MINIMUM LIFE EXPECTANCY OF 5 YEARS