

NOTES:

- 1. THE CABLES SHALL BE PERMANENTLY MARKED WITH MANUFACTURERS IDENTIFICATION, YEAR OF MANUFACTURE AND VOLTAGE RATING AT INTERVALS ALONG THE OUTER PVC SHEATH OF THE CABLE.
- THE CABLE SHALL ALSO HAVE ITS LENGTH PRINTED AT INTERVALS ALONG THE SACRIFICIAL SHEATH, CONSISTING OF CONSECUTIVE NUMBERS, NOMINALLY SPACED AT ONE METRE.
- CABLE TO BE WOUND ON DRUM TO ENSURE LEGIBILITY OF ABOVE INFORMATION IN NOTES 1 AND 2.
- 4. CABLE WILL COMPLY WITH AS 3198 AND AS 1125.
- 5. CABLE CURRENT RATINGS AS PER AS/NZS 3008
- 6. FOR USE AS HV DROPPER CABLE FROM BOTTOM OF EDO OR LINKS TO TRANSFORMER, OR SURGE DIVERTERS ETC.
- 7. MINIMUM OF 2mm TOTAL INSULATION FOR INADVERTENT CONTACT.
- 8. TO COMPLY WITH STSP 02-002.

ITEM	UNITS	1	2	3
ITEM NUMBER	-	407083	406733	503088
CONDUCTOR AREA	sq.mm	35	70	150
NOMINAL CONDUCTOR STRANDING	mm	7/2.52	19/2.17	37/2.27
CONDUCTOR DIAMETER	mm	7.6	10.7	15.9
INSULATION THICKNESS	mm	0.9	1.1	1.4
MINIMUM PVC SHEATH THICKNESS	mm	1.4	1.4	1.6
OVERALL DIAMETER	mm	12.7	16.0	22.5
STANDARD DRUM LENGTH	m	500	500	1000
MASS OF CABLE	kg/m	0.406	0.753	1.534
CONDUCTOR FORM	-		ED NON-COM HARD DRAWI	
OUTER SHEATH COLOUR	-	BLACK		
MAX. PULLING TENSION (EYE)	kN	2.45	1	10.5
BENDING RADIUS - TENSION	mm	152	192	270
BENDING RADIUS - NON-TENSION	mm	101	128	180
CURRENT RATING - IN AIR 1m/s WIND	А	203	305	477
DC RESISTANCE @ 20 DEG. C	Ohms/km	0.540	0.276	0.128
VOLTAGE DROP	mA/Am	1.18	_	0.33

סככ	DOWED STANDARD DRAWING		
TAG REFERENCE	DESCRIPTION		
	COPPER CONDUCTOR, STRANDED NON-COMPACTED CIRCULAR HARD DRAWN C11000		
2	EXTRUDED XLPE - WHITE		
3	UV STABLISED EXTRUDED PVC 5V-90		

	AMENDMENTS				
NO	DESCRIPTION	DRN	DATE	CKD	APPD
Α	ISSUED	A.S.	MAR'06	C.C.	C.C.
1	NOTE 5 ADDED, ITEMS 2 AND 3 ADDED	A.T.	MAR'15	I.B.	B.C.
2	TITLEBLOCK & DRAWING NUMBER FORMATTED	K.T.	JAN'19	c.c.	c.c.
3	BENDING RADIUS AMENDED	H.E.	APR'20	B.C.	B.C.
	APPLICATION TO NOTES 6 & 7. ADDED NOTE 8.				
4	REFORMATTED TABLES. UPDATED TECHNICAL DATA. MOVED DESIGN	A.N.	OCT'21	A.N.	B.V.



ITCL				
DES	-	POWER STANDARD DRAWING		
DRN	K.IBBOTT	0.6/1KV		
CKD	C.CAMILLERI			
APPD	C.C.			
SCALE	NTS		XLPE - PVC	
ISSUED	MARCH '06	А3	DRAWING COS OF A SE	
ALL DIM	A. IN mm	AS	NUMBER S02-01-01-35 /4	
DRAFTING STANDARD TO A.S.1100 CAD PRODUCT - DO NOT AMEND MAN			CAD PRODUCT - DO NOT AMEND MANUALLY AMDT	