



- LETTERING : "OPEN" 38W x 25H x 3 THICK  
"CLOSE" 30W x 20H x 5.5 THICK

- LETTERING : "DANGER" 16W x 20H x 5 THICK.  
7W x 14H x 3 THICK

- LETTERING : "DANGER" 7W x 14H x 3 THICK

- LETTERING : 33W x 35H x 10 THICK

OBSOLETE

REFER TO NOTE

NOTE: PADLOCK STANDARD  
DANGER/DO NOT OPERATE  
TAG TO POLE.

- MATERIAL TO BE 1.0mm THICK ALUMINIUM.
- COLOURS AS SHOWN
- FINISH SHALL BE TWO COATS (PER COLOUR) OF ENAMEL PAINT TO AS K126.
- FOR OUTDOOR USE UNDER EXTREME TROPICAL CONDITIONS.
- SIGN IS TO HAVE A LIFE EXPECTANCY OF 20 YEARS.

AMENDMENTS		DRN	DATE	CKD	APPD
1	ADD NOTE DWG OBSOLETE	K.I	NOV '05	C.C.	C.C.
0	ISSUED FOR CONSTRUCTION	A.S	OCT '02	R.C.	M.B.
NO	DESCRIPTION	DRN	DATE	CKD	APPD



DES	M. BOCK
DRN	A. SCHMID
CKD	M. BOCK
APPD	M. BOCK
SCALE	1:2
ISSUED	OCT '02
ALL DIM.	IN mm
DRAFTING STANDARD	TO A.S. 1100

POWER STANDARD DRAWING	
SIGN WARNING	
SF6 GAS LOAD BREAK SWITCH	
A3	DRAWING NUMBER S02-1-8-18
DRAFTING STANDARD TO A.S. 1100	
CAD PRODUCT - DO NOT AMEND MANUALLY	
AMDT	