



NOTES :

1. SIGN MUST HAVE A MINIMUM LIFE EXPECTANCY OF 5 YEARS.
2. MATERIAL TO BE 2.0 mm ANODIZED ALUMINIUM.
3. SIGN TO BE IN ACCORDANCE WITH AS 1319 UNLESS OTHERWISE SPECIFIED. ANY GRAPHIC SYMBOL IS TO BE IN ACCORDANCE WITH AS 1104.
4. LETTERING TO BE SERIES 'D' TO AS 1744.
HEIGHT : 'WARNING' - 30 mm
TABLE WORDING SIZE TO BE 25 mm MINIMUM.
5. FINISH SHALL BE 1 COAT PRIMER 2 COATS (PER COLOUR) OF VITREOUS ENAMEL PAINT TO AS 4025 PARTS 1 & 4
OR
3M SCOTCHLITE CLASS 2 SHEETING AND 3M INKS TO GIVE A LIFE EXPECTANCY OF 5 YEARS MINIMUM.
ALTERNATIVE FINISHES WILL BE CONSIDERED PROVIDED THAT SUCH FINISHES ARE CAPABLE OF WITHSTANDING SEVERE TROPICAL CONDITIONS ESPECIALLY ULTRA-VIOLET LIGHT. WHERE ALTERNATIVE FINISHES ARE PROPOSED COMPLETE TECHNICAL INFORMATION AND DETAILS OF PERFORMANCE SHALL BE PROVIDED TO FACILITATE TECHNICAL ASSESSMENT.
6. COLOUR :
BACKGROUND : WHITE
DANGER PANEL : WHITE LETTERS ON RED OVAL SHALL BE ON A BLACK BACKGROUND WITH WHITE BORDER DEFINING THE OVAL. THERE SHALL BE A NARROW BLACK BORDER AROUND THE PERIMETER OF THE SIGN. ALL OTHER WORDING TO BE IN BLACK.
RED BACKGROUND : SIGNAL RED TO CODE R13 IN ACCORDANCE WITH AS 2700.

NO	DESCRIPTION	DRN	DATE	CKD	APPD
1.	ISSUED FOR CONSTRUCTION	K.J.	APR 05	C.C.	C.C.
AMENDMENTS					



DES	...	POWER STANDARD DRAWING			
DRN	K.I.	SIGNS PORTABLE GENERAL WARNING			
CKD	C.C.				
APPD	C.C.				
SCALE	...				
ISSUED	MAR 05	A3	DRAWING NUMBER	S2-1-8-26	
ALL DIM. IN mm					
DRAFTING STANDARD TO A.S.1100		CAD PRODUCT — DO NOT AMEND MANUALLY		AMDT	