



**BAR - DEFORMED (GRADE 500N)**

**NOTES**

1. DEFORMED BAR TO BE IN ACCORDANCE WITH AS/NZS 4671.
2. DEFORMED BAR SHALL BE GRADE 500N. MINIMUM 175 mm THREAD (TO AS 1275) SHALL BE CUT STRICTLY IN ACCORDANCE WITH TEMPCORE INSTRUCTIONS.
3. THE 175 mm THREADED SECTION OF THE DEFORMED BAR SHALL BE HOT DIPPED GALVANISED IN ACCORDANCE WITH AS 1650.
4. NUTS AND WASHERS (TO AS 1252) TO BE GRADE 8.8, GALVANISED AND FIRM FITTING ON CORROSION PROTECTED THREAD.

ITEM	STOCK CODE	DIM. 'A'	DIA. 'B'	THREAD
1	196071	1200	20	M20
2	196089	1300	24	M24
3	196055	1600	24	M24
4	196063	2100	36	M36

**REFERENCE DRAWINGS**

- S3-1-2-1 - RAG BOLT REINFORCEMENT TYPE 5 AND TYPE 9.  
S3-1-2-2 - RAG BOLT REINFORCEMENT TYPE 12 AND TYPE 18.

5 UPDATED TO AS/NZS 4671 4 NOTES AMENDED 3 NOTE 3 REWORDED FOR CLARIFICATION. 2 FLAT WASHER NOW 'EXTRA LARGE' NOW 'LARGE' (AS PER AS 1237) 1 FLAT WASHER NOW 'EXTRA LARGE' AND NOTES REVISED					 NORTHERN TERRITORY	DES	g.mck	<b>N.T. STANDARD</b>			
						DRN	G.McKINNON	<b>RAG BOLT REINFORCEMENT BAR - DEFORMED FABRICATION DETAILS</b>			
						CKD	G.SCHUBERT				
						APPD	B.T.KENT				
						ISSUED	JAN'88	<b>A3</b>	DRAWING NUMBER	<b>S3-1-2-6</b>	
				DRAFTING STANDARD TO AS 1100							
				ALL DIM IN mm		SCALE		N.T.S.	SHEET	AMDT	
No.	AMENDMENT				DRAWN	CH'KD	APPD	DATE			