


**NOTES:**

1. SIGN IS FOR OUTDOOR USE UNDER EXTREME TROPICAL CONDITIONS AND MUST HAVE A MINIMUM LIFE EXPECTANCY OF 20 YEARS.
2. MATERIAL TO BE 2.0 mm ANODIZED ALUMINIUM.
3. SIGN TO BE IN ACCORDANCE WITH AS1319 UNLESS OTHERWISE SPECIFIED. ANY GRAPHIC SYMBOL IS TO BE IN ACCORDANCE WITH AS1104.
4. LETTERING TO BE SERIES 'D' TO AS1744.  
HEIGHT : 'DANGER' - 30 mm  
OTHER WORDING SIZE TO BE 14mm MINIMUM.
5. FINISH SHALL BE 1 COAT PRIMER, 2 COATS (PER COLOUR) OF VITREOUS ENAMEL PAINT TO AS4025 PARTS 1 & 4 OR 3M SCOTCHLITE CLASS 2 SHEETING AND 3M INKS TO GIVE A LIFE EXPECTANCY OF 5 YEARS MINIMUM.  
ALTERNATIVE FINISHES WILL BE CONSIDERED PROVIDED THAT SUCH FINISHES ARE CAPABLE OF WITHSTANDING SEVERE TROPICAL CONDITIONS ESPECIALLY ULTRA-VIOLET LIGHT. WHERE ALTERNATIVE FINISHES ARE PROPOSED, COMPLETE TECHNICAL INFORMATION AND DETAILS OF PERFORMANCE SHALL BE PROVIDED TO FACILITATE TECHNICAL ASSESSMENT.
6. COLOUR:  
BACKGROUND : WHITE  
DANGER PANEL : WHITE LETTERS ON RED OVAL SHALL BE ON A BLACK BACKGROUND WITH WHITE BORDER DEFINING THE OVAL. THERE SHALL BE A NARROW BLACK BORDER AROUND THE PERIMETER OF THE SIGN. ALL OTHER WORDING TO BE IN BLACK.  
RED BACKGROUND : SIGNAL RED TO CODE R13 IN ACCORDANCE WITH AS2700.
7. STOCK CODE .....

1	APPROVED FOR CONSTRUCTION.	RG1	SEP'99	MWB	FRR
NO	DESCRIPTION	DRN	DATE	CKD	APPD
AMENDMENTS					

					
NORTHERN TERRITORY					

DES	W. BOCK
DRN	R. INNES
CKD	S. SAWYER
APPD	F. ROBSON
SCALE	1:1.25
ISSUED	20/10/97
ALL DIM.	IN mm

POWER STANDARD DRAWING	
SINGLE WIRE EARTH RETURN EARTHING DANGER SIGN POST MOUNTED	
A3	DRAWING NUMBER S25-3-2-02
DRAFTING STANDARD TO A.S.1100	
CAD PRODUCT - DO NOT AMMEND MANUALLY	
	